



- GRIDWORX STANDARD L-BRACKET (CONTINUOUS) L002
- GRIDWORX PLANX REBATED SADDLE CLIP 306
- FOAM TAPE APPLIED TO GRIDWORX L BRACKET C002
- CONTINUOUS SEALANT IN KERF
- GRIDWORX PROPRIETARY HIGH STRENGTH, FAST CURE STP (SILANE TERMINATED POLYETHER) ADHESIVE/SEALANT
- 1/4" X 1-1/2" (16" O.C. MAX) F203
- TOP COURSE ANCHOR 003
- EXTENDED TOP COURSE ANCHOR 103
- THERMAL BREAKING SLEEVE WASHER C300
- 1/4" X 1-1/8" F201
- INSULATION (BY OTHERS)
- GRIDWORX ADJUSTABLE VERTICAL MULLION 16" O.C. A211 A214 A212 A215 A216
- GRIDWORX ADJUSTABLE DISCRETE GIRT SUPPORT (16" O.C. HORIZONTAL 24" O.C. VERTICAL) A202 A203 A204 A205
- THERMAL BREAKING BACK PLATE C311
- 1/4" X 2-1/2" FOR STEEL STUD F205
- 1/4" X 2-1/4" FOR CONCRETE/CMU F104
- 1/4" X 3" FOR WOOD STUD F505
- FASTENER 24" OC VERTICAL SPACING
- WATER PROOFING (BY OTHERS)

DIM. VARIES PER PROJECT
 DIM. VARIES PER PROJECT
 DIM. VARIES PER PROJECT
 ADJUSTABLE 2'-5"
 OPTIONAL FOR EXTERIOR INSULATION
 DIM. VARIES PER PROJECT
 STEEL, CONCRETE, OR WOOD SUBSTRATE

THERMALLY BROKEN SUBFRAME
 TOP ANCHOR SECTION DETAIL

PLANX SYSTEM
DATE:
NOTES:
SCALE: 1:1
TITLE:
SHEET: