

**THERMALLY BROKEN SUBFRAME**  
 SOFFIT SECTION DETAIL

- THERMAL BREAKING SLEEVE WASHER (C300)
- THERMAL BREAKING BACK PLATE (C311)
- 1/4" X 2-1/2" FOR STEEL STUD (F205)
- 1/4" X 2-1/4" FOR CONCRETE/CMU (F104)
- 1/4" X 3" FOR WOOD STUD (F505)
- FASTENER 24" OC VERTICAL SPACING
- INSULATION (BY OTHERS)
- GRIDWORX ADJUSTABLE DISCRETE GIRT SUPPORT (16" O.C. HORIZONTAL 24" O.C. VERTICAL) (A202, A203, A204, A205)
- 1/4" X 1-1/8" (F201)
- 1/4" X 1-1/2" (16" O.C. MAX) (F203)
- GRIDWORX ADJUSTABLE VERTICAL MULLION 16" O.C. (A211, A212, A214, A215, A216)
- FULL BEARING HI-IMPACT RESISTANT PLASTIC SHIM(S) FIELD VERIFY (AS NEEDED, 5/8" MAX)
- WIND LOAD SUBSTRATE ANCHOR (503)
- CONTINUOUS SILICONE IN KERF
- WIND LOAD PANEL ANCHOR (502)
- GRIDWORX PROPRIETARY HIGH STRENGTH, FAST CURE STP (SILANE TERMINATED POLYETHER) ADHESIVE/SEALANT
- KEIL 8.5 MM UNDERCUT ANCHOR (F352)

