



- WATER PROOFING (BY OTHERS)
- 1/4" X 1-1/2" (16" O.C. MAX) (F203)
- INSULATION (BY OTHERS)
- STARTER J ANCHOR (001)
- EXTENDED STARTER J ANCHOR (101)
- WEEP HOLES
- WEEP MESH 24" O.C.
- LOW MODULUS SILICONE W/ BACKER ROD
- GRIDWORX L BRACKET (L001) (L003)
- FOAM TAPE APPLIED TO GRIDWORX L BRACKET (C001) (C002)
- CONTINUOUS SEALANT IN KERF
- TOP COURSE ANCHOR (003)
- EXTENDED TOP COURSE ANCHOR (103)
- 1/4" X 1-1/2" (16" O.C. MAX) (F203)
- 1/4" X 1-1/8" (F201)
- GRIDWORX ADJUSTABLE VERTICAL MULLION 16" O.C. (A211) (A212) (A213) (A214) (A215)
- GRIDWORX ADJUSTABLE DISCRETE GIRT SUPPORT (16" O.C. HORIZONTAL) (24" O.C. VERTICAL) (A202) (A203) (A204) (A205)
- THERMAL BREAKING BACK PLATE (C311)
- THERMAL BREAKING SLEEVE WASHER (C300)
- 1/4" X 2-1/2" FOR STEEL STUD (F205)
- 1/4" X 2-1/4" FOR CONCRETE/CMU (F104)
- 1/4" X 3" FOR WOOD STUD (F505)
- FASTENER 24" OC VERTICAL SPACING

**THERMALLY BROKEN SUBFRAME**  
 DEFLECTION JOINT SECTION DETAIL

KERF SYSTEM
DATE:
NOTES:
SCALE: 1:1
TITLE:
SHEET: